**SAFETY DATA SHEET** 

MATERIAL NAME: HYLOMAR M AEROSOL 710XX362

EMERGENCY TELEPHONE NO.: CALL INFOTRAC AT 1-800-535-5053

**PRODUCT INFORMATION NO.: (513) 874-6550** 

**DATE ISSUED: FEBRUARY 1, 2018** 

## **SECTION 1 – GENERAL INFORMATION**

MANUFACTURER'S NAME: HYLOMAR LTD

ADDRESS: CALE LANE, NEW SPRINGS WIGAN WN2 1JT

TRADE NAME & SYNONYMS: NONE

**USES:** Non-Setting and Non-Hardening Gasketing Compound

SHELF LIFE: 2 YEARS

#### SECTION 2 - HAZARDOUS INGREDIENTS/IDENTITY INFORMATION

#### CLASSIFICATION OF THE SUBSTANCE OR MIXTURE

The mixture has been assessed and/or tested for its physical, health and environmental hazards and the following classification applies.

## CLASSIFICATION ACCORDING TO DIRECTIVE 67/548/EEC OR 1999/45/EC AS AMENDED

Classification F+,R12, Xi,R36, R66-67

The full text for all R-phrases is displayed in section 16.

#### CLASSIFICATION ACCORDING TO REGULATION (EC) NO 1272/2008 AS AMENDED

PHYSICAL HAZARDS

Flammable aerosols Category 1 Extremely flammable aerosol

**HEALTH HAZARDS** 

Seroius eye damage/eye irritation Category 2 Causes serious eye irritation

Specific target organ toxicity-single Category 2 (Central Nervous May cause damage to organs

exposure system) (Central Nervous System)

Specific target organ toxicity-single Category 3 narcotic effects May cause drowsiness or

exposure dizziness

HAZARD SUMMARY

PHYSICAL Extremely flammable

**HEALTH** Irritating to eyes. Repeated exposure may cause skin dryness or cracking.

Vapors may cause drowsiness and dzziness

**ENVIRONMENTAL** Not classified for hazards to the environment

SPECIFIC HAZARDS When sprayed on a naked flame or any incandescent material the aerosol

vapors can be ignited. Aerosol containers can explode when heated due to excessive pressure build-up. Causes severe eye irritation. Vapors may cause

drowsiness and dizziness

MAIN SYMPTOMS Exposed may experience eye tearing, redness and discomfort. Prolonged and/or

repeated skin contact may result in mild irritation or redness. Vapors may cause

drowsiness and dizziness. Symptoms of overexposure may be headache,

dizziness, tiredness, nausea and vomiting

**SAFETY DATA SHEET** 

MATERIAL NAME: HYLOMAR M AEROSOL 710XX362

EMERGENCY TELEPHONE NO.: CALL INFOTRAC AT 1-800-535-5053

**PRODUCT INFORMATION NO.: (513) 874-6550** 

**DATE ISSUED: FEBRUARY 1, 2018** 

# SECTION 2 - HAZARDOUS INGREDIENTS/IDENTITY INFORMATION (CONT)

#### **LABEL ELEMENTS**

#### LABEL ACCORDING TO REGULATION (EC) No. 1272/2008 AS AMENDED

CONTAINS: Acetone, Dimethyl ether



SIGNAL WORD: Danger

**HAZARD STATEMENTS:** Extremely flammable aerosol. Causes serious eye irritation. May cause

drowsiness or dizziness. May cause damage to organs (Central nervous

system)

#### PRECAUTIONARY STATEMENTS

PREVENTION Keep away from heat/sparks/open flames/hot surfaces. No smoking.

Pressurized container: Do not pierce or burn, even after use. Do not

spray on an open flame or other ignition source. Do not breath mist/vapor/spray. Wear eye/face protection. Use only outdoors or in a well-ventilated area. Do not eat, drink or smoke when using this product. Wash thoroughly after handling

RESPONSE If exposed and you do not feel well, call a Poison Center or physician. If in

eyes rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing. If eye irritation persists, seek medical attention. If inhaled remove to fresh air and keep at rest in a position comfortable for breathing. Call a Poison Center or physican if you feel unwell

STORAGE Store locked up. Store in a well-ventilated place. Keep container tightly closed.

Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F

**DISPOSAL** Dispose of contents/container in accordance with local/regional/ national/

international regulations

## SUPPLEMENTAL LABEL INFORMATION

Repeated exposure may cause skin dryness or cracking

OTHER HAZARDS Not assigned

**SAFETY DATA SHEET** 

MATERIAL NAME: HYLOMAR M AEROSOL 710XX362

EMERGENCY TELEPHONE NO.: CALL INFOTRAC AT 1-800-535-5053

**PRODUCT INFORMATION NO.:** (513) 874-6550

**DATE ISSUED: FEBRUARY 1, 2018** 

## **SECTION 3 - COMPOSITION**

#### **MIXTURE**

#### **GENERAL INFORMATION**

CHEMICAL NAME % CAS NO/EC NO REACH REGISTRATION# INDEX#

Acetone 25-50 67-64-1 606-001-00-8

200-662-2

CLASSIFICATION: DSD: F;R11, Xi;R36, R66-67

CLP: Flam. Liq. 2;H225, Eye Irrit. 2:H319, STOT SE 3;H336

Dimethyl ether 25-50 115-10-6 603-019-00-8

204-065-8 **CLASSIFICATION: DSD:** F+:R12

**CLP:** Flam. Gas 1;H220, Eye Irrit. 2;H319, STOT SE 2;H371

CLP: Regulation No. 1272/2008 DSD: Directive 67/548/EEC

COMPOSITION COMMENTS: The full test for all R- and H- phrases is displayed in Section 16. All

concentrations are in percent by weight unless ingredient is a gas.

Gas concentrations are in percent by volume

SECTION 4 - FIRST AID

GENERAL INFORMATION: Ensure that medical personnel are aware of the material(s) involved and take

precautions to protect themselves

DESCRIPTION OF FIRST AID MEASURES:

**INHALATION:** Move into fresh air and keep at rest. If not breathing, give CPR or give oxygen

by trained personnel. Get medical attention if any discomfort continues

**SKIN CONTACT:** Take off immediately all contaminated clothing. Wash skin thoroughly with

soap and water. If irritation persists get medical attention

EYE CONTACT: Flush eyes thoroughly with water for at least 15 minutes. Remove any contact

lenses. Get medical attention if any discomfort continues

INGESTION: Rinse mouth thoroughly. Drink a few glasses of water or milk. Get medical

attention if discomfort continues

MOST IMPORTANT SYMPTOMS ACUTE AND DELAYED:

Exposed may experience eye tearing, redness, and discomfort. Prolonged

and/or repeated skin contact may result in mild irritation or redness. Vapours may cause drowsiness and dizziness. Symptoms of overexposure may be

headache, dizziness, tiredness, nausea and vomiting

MEDICAL ATTENTION: Provide general supportive measures and treat symptomatically. In case of

shortness of breath, give oxygen

#### **SECTION 5 - FIRE FIGHTING MEASURES**

GENERAL FIRE HAZARDS Extremely flammable

Extremely flammable aerosol-contents under pressure. Aerosol containers can explode when heated due to excessive pressure build-up. The product is extremely flammable, and explosive vapor/air mixtures may be formed even at normal room temperatures. Vapors are heavier than air and may travel along the ground to some distant source of ignition and flash back

**SAFETY DATA SHEET** 

MATERIAL NAME: HYLOMAR M AEROSOL 710XX362

EMERGENCY TELEPHONE NO.: CALL INFOTRAC AT 1-800-535-5053

**PRODUCT INFORMATION NO.: (513) 874-6550** 

**DATE ISSUED: FEBRUARY 1, 2018** 

#### SECTION 5 - FIRE FIGHTING MEASURES (CONT)

**EXTINGUISHING MEDIA** 

SUITABLE MEDIA Water spray, foam, dry powder or carbon dioxide

**UNSUITABLE MEDIA**Do not use water jet as an extinguisher, as this will spread the fire

SPECIAL HAZARDS Aerosol containers can explode when heated, due to excessive pressure build-

up. By heating and fire, harmful vapors/gases may be formed

SPECIAL PROTECTIVE

EQUIPMENT

Self-contained breathing apparatus and full protective clothing must be worn in case of fire. Selection of respiratory protection for fire fighting: follow the

general fire precautions indicated in the workplace

SPECIAL PROCEDURES Cool containers exposed to heat with water spray and remove container if no

risk is involved. Prevent runoff from fire control or dilution from entering streams,

sewers or drinking water supply

## **SECTION 6 - ACCIDENTAL RELEASE MEASURES**

#### PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES

NON-EMERGENCY PERSONNEL Keep upwind. Ventilate closed spaces before entering them. Avoid inhalation of

vapors/spray and contact with skin and eyes. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Keep

unnecessary personnel away

EMERGENCY RESPONDERS Keep unnecessary personnel away. Wear protective clothing as described in

Section 8 of this safety data sheet

**ENVIRONMENTAL PRECAUTIONS** Prevent further leakage or spillage if safe to do so. Do not discharge into drains,

water courses or onto the ground

**CLEAN UP METHODS** Eliminate all ignition sources. Ventilate the area. Wipe up with absorbent material

(cloth, fleece). Transfer to a container for disposal. Following product recovery,

Flush area with water

REFERENCE TO OTHER SECTIONS For personal protection, see section 8. For waste disposal, see section 13

#### SECTION 7 - HANDLING AND STORAGE

#### PRECAUTIONS FOR SAFE HANDLING:

Keep away from sources of ignition-No smoking. Use non-sparking tools and explosion-proof equipment. Vapors may form explosive mixtures with air. Use only outdoors or in a well-ventilated area. Avoid inhalation of vapors and spray mist. Avoid contact with skin and eyes. Wear protective clothing as described in Section 8. Avoid prolonged exposure. Wash thoroughly after handling. Wash contaminated clothing before reuse. Observe good industrial hygiene practices

CONDITIONS FOR SAFE STORAGE: Pressurized container: Must not be exposed to temperatures above 50°C or

122°F. Aerosol containers can explode when heated due to excessive pressure build-up. Keep away from heat, spark, open flames and other sources of ignition. Do not puncture, incinerate or crush. Avoid exposure to long periods of sunlight. Keep containers tightly closed in a dry, cool and well-

ventilated place. Keep locked up

SPECIFIC USES: Non-setting and non-hardening gasketing compound

**SAFETY DATA SHEET** 

MATERIAL NAME: HYLOMAR M AEROSOL 710XX362

EMERGENCY TELEPHONE NO.: CALL INFOTRAC AT 1-800-535-5053

**PRODUCT INFORMATION NO.: (513) 874-6550** 

**DATE ISSUED: FEBRUARY 1, 2018** 

## **SECTION 8 - PERSONAL PROTECTION**

#### **CONTROL PARAMETERS**

OCCUPATIONAL EXPOSURE LIMITS

**UK.EH40 WORKPLACE EXPOSURE LIMITS (WELs)** 

COMPONENETS	TYPE	VALUE	
Acetone	TWA	1210 mg/m3	
	STEL	1500 ppm	
		3620 mg/m3	
Dimethyl ether (115-10-6)	TWA	500 ppm	
	TWA	400 ppm	
	STEL	500 ppm	
	TWA	766 mg/m3	
	STEL	958 mg/m3	

EU. INDICATIVE EXPOSURE AND DIRECTIVES RELATIONG TO THE PROTECTION OF RISKS RELATED TO WORK EXPOSURE TO CHEMICAL, PHYSICAL AND BIOLOGICAL AGENTS.

COMOPONENTS	TYPE	VALUE
Acetone (67-64-1)	TWA	1210 mg/m3 550 ppm
Dimethyl ether (115-10-6)	TWA	1000 ppm 1920 mg/m3
RECOMMENDED MONITORING:	Follow standard monitoring procedures	
DNEL	Not available	
PNEC	Not available	
EVECUEE CONTROL S		

EXPOSURE CONTROLS

**ENGINEERING CONTROLS** Provide adequate ventilation. Observe Occupational Exposure Limits and

minimize the risk of inhalation of vapors

PERSONAL PROTECTIVE EQUIPMENT

GENERAL INFORMATION Personal protective equipment should be chosen according to the CEN

standards and in discussion with the supplier of the personal protective

equipment

EYE/FACE PROTECTION: If eye contact is likely, safety glasses with side shields or chemical type

goggles should be worn

HAND PROTECTION: Wear protective gloves. Butyl rubber gloves are recommended. Breakthrough

time > 120 min. Be aware that the liquid may penetrate the gloves. Frequent change is advisable. Suitable gloves can be recommended by the glove

supplier

OTHER: Normal work clothing (long sleeved shirts and long pants) is recommended

**RESPIRATORY PROTECTION:** In case of inadequate ventilation or risk of inhalation of vapors, use suitable

respiratory equipment with gas filter (type A2). If engineering controls do not maintain airborn concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have

not been established), an approved respirator must be worn

THERMAL HAZARDS: Not applicable

HYGIENE MEASURES: Always observe good personal hygiene measures, such as washing after

handling the material and before eating, drinking and/or smoking. Routinely wash work clothing and protective equipment to remove contaminant.

ENVIRONMENTAL EXPOSURE: Environmental manager must be informed of all major releases

**SAFETY DATA SHEET** 

MATERIAL NAME: HYLOMAR M AEROSOL 710XX362

EMERGENCY TELEPHONE NO.: CALL INFOTRAC AT 1-800-535-5053

**PRODUCT INFORMATION NO.: (513) 874-6550** 

**DATE ISSUED: FEBRUARY 1, 2018** 

#### **SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES**

#### INFORMATION ON BASIC PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE Aerosol Blue thixotropic gel PHYSICAL STATE Liquid

FORM Aerosol thixotropic gel COLOR Blue

ODOR Sweet, Ethereal ODOR THRESHOLD Not Available

pH Not Applicable MELTING POINT Not Available

FREEZING POINT Not Available BOILING POINT Not Applicable

FLASH POINT -41°C(-41.8°F) Closed Cup AUTO IGNITION TEMP Not Available

FLAMMABILITY Not Applicable OXIDIZING PROPERTIES Not Available

(SOLID,GAS)

FLAMMABILITY 3.4 EXPLOSIVE PROPERTIES Not Available

Limit –lower(%)
FLAMMABILITY 57 EXPLOSIVE LIMIT Not Available

Limit-upper (%)

VAPOR PRESSURE 185 (20°C/68°F) EVAPORATION RATE Not Applicable

RELATIVE DENSITY 1.03 (20°C/68°F) SOLUBILITY(WATER) Insoluble

PARTITION COEFFICIENT Not Available DECOMPOSITION Not Available

(n-octanol/water) temperature

VISCOSITY Not Applicable VOC(WEIGHT%) 40-44

(Hylomar test method 1.1A Determination

of Volatile Matter)

PERCENT VOLATILE Not Available

OTHER INFORMATION No relevant additional information available

## **SECTION 10 - STABILITY AND REACTIVITY**

REACTIVITY This product is stable and non reactive under normal conditions of use, storage and

transport

CHEMICAL STABILITY Risk of ignition. Material is stable under normal conditions

POSSIBILITY OF No dangerous reaction known under normal conditions of use

**HAZARDOUS REACTIONS** 

CONDITIONS TO AVOID Heat, flames, sparks. Pressurized container. Must not be exposed to temperatures above

50°C (122°F). Protect against direct sunlight

INCOMPATIBLE MATERIALS

Strong oxidizing agents

HAZARDOUS DECOMPOSITION PRODUCTS Thermal decomposition or combustion may liberate carbon oxides and other toxic

gases or vapors

SAFETY DATA SHEET

MATERIAL NAME: HYLOMAR M AEROSOL 710XX362

EMERGENCY TELEPHONE NO.: CALL INFOTRAC AT 1-800-535-5053

**PRODUCT INFORMATION NO.: (513) 874-6550** 

**DATE ISSUED: FEBRUARY 1, 2018** 

**SECTION 11 - TOXICOLOGICAL INFORMATION** 

GENERAL INFORMATION Occupational exposure to the substance or mixture may cause adverse effects

**ROUTES OF EXPOSURE** 

**INGESTION** Ingestion may cause irritation and discomfort

INHALATION Vapors may cause drowsiness and dizziness. In high concentrations, vapors may be

irritating to the respiratory system

**SKIN CONTACT** Prolonged or repeated skin contact may cause drying, cracking or irritation

**EYE CONTACT** Causes serious eye irritation

**SYMPTOMS** Exposed may experience eye tearing, redness, and discomfort. Prolonged and/or repeated

> skin contact may result in mild irritation or redness. Vapors may cause drowsiness and dizziness. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and

vomiting

INFORMATION ON TOXICOLOGICAL EFFECTS

**ACUTE TOXICITY** May cause discomfort if swallowed

**COMPONENTS TEST RESULTS** 

Dimethyl Ether (115-10-6) Acute inhalation LC50 Rat: 308.5 mg/l 4 hours Acetone (67-64-1) Acute dermal LD50 Rabbit: 20000 ,g/kg

Acute inhalation LC50 Rat: 50 mg/l 8 hours

Acute oral LD50 Rat: 5800 mg/kg

SKIN IRRITATION Prolonged or repeated skin contact may cause drying, cracking or irritation

EYE DAMAGE/IRRITATION Causes serious eye irritation

RESPIRATORY Not classified

**SENSITISATION** 

**GERM CELL MUTAGENICITY** Not classified

CARCINOGENICITY Not classified

REPRODUCTIVE

**TOXICITY** 

Not classified

TARGET ORGAN

**TOXICITY SINGLE** 

**EXPOSURE** 

May cause drowsiness or dizziness. May cause damage to organs: Central Nervous

System

TARGET ORGAN **TOXICITY REPEATED** 

**EXPOSURE** 

Not classified

**ASPIRATION HAZARD** Not classified

MIXTURE VS SUBSTANCE Not classified

INFORMATION

OTHER INFORMATION No other specific acute or chronic health impact noted

**SAFETY DATA SHEET** 

MATERIAL NAME: HYLOMAR M AEROSOL 710XX362

EMERGENCY TELEPHONE NO.: CALL INFOTRAC AT 1-800-535-5053

**PRODUCT INFORMATION NO.: (513) 874-6550** 

**DATE ISSUED: FEBRUARY 1, 2018** 

#### **SECTION 12 - ECOLOGICAL INFORMATION**

#### TOXICITY

COMPONENTS TEST RESULTS

ACETONE (67-64-1) LC50 Fathead minnow (Pimpephales promelas): >100 mg/l

96 hours

PERSISTENCE AND

DEGRADABILITY

Not available

BIOACCUMULATIVE POTENTIAL

Not available

MOBILITY The acetone component is miscible with water and may spread in water systems

ENVIRONMENTAL FATE PARTITION COEFFICIENT

Not available

MOBILITY IN SOIL Not available

RESULTS OF PBT AND VPvB ASSESSMENT Not a PBT or vPvB substance or mixture

OTHER ADVERSE

**EFFECTS** 

The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment. An environmental hazard cannot be excluded in the event of unprofessional

handling or disposal.

# **SECTION 13 - DISPOSAL**

#### **WASTE TREATMENT METHODS**

**RESIDUAL WASTE**Do not discharge into rivers, lakes, mountains, etc. because the product may affect the

environment

CONTAMINATED PACKAGING

Empty containers should be taken to an approved waste handling site for recycling or

disposal

**EU WASTE CODE** The waste code should be assigned in discussion between the user, the producer and the

disposal company

**DISPOSAL METHODS** Do not discharge into drains, water courses or onto the ground. Collect and reclaim or

dispose in sealed containers at licensed waste disposal site. Dispose of contents/container

in accordance with local/regional/national/international regulations

## **SECTION 14 - TRANSPORTATION**

## ADR

UN Number UN1950 UN PROPER SHIPPING NAME AEROSOLS

Transport Hazard Class(es) 2.1
Subsidiary class(es) Environmental Hazards No
Labels Required 2.1

**Special Precautions** Read safety instructions, SDS and emergency procedures before handling

Special Precautions Read safety instructions, SDS and emergency procedures before handling

Environmental Hazards No Labels Required 2.1

**Special Precautions** Read safety instructions, SDS and emergency procedures before handling

8 of 10

SAFETY DATA SHEET

MATERIAL NAME: HYLOMAR M AEROSOL 710XX362

EMERGENCY TELEPHONE NO.: CALL INFOTRAC AT 1-800-535-5053

**PRODUCT INFORMATION NO.:** (513) 874-6550

**DATE ISSUED: FEBRUARY 1, 2018** 

#### **SECTION 14 - TRANSPORTATION (CONT)**

RID

UN Number UN1950 UN PROPER SHIPPING NAME AEROSOLS

Transport Hazard Class(es) 2.1
Subsidiary class(es) Environmental Hazards No
Labels Required 2.1

ADN

**UN Number** UN1950 **UN PROPER SHIPPING NAME** AEROSOLS

Transport Hazard Class(es) 2.1 Subsidiary class(es) -

IATA

UN Number UN1950

UN PROPER SHIPPING NAME AEROSOLS, FLAMMABLE

Transport Hazard Class(es) 2.1
Subsidiary class(es) Environmental Hazards No
Labels Required 2.1

Special Precautions Read safety instructions, SDS and emergency procedures before handling

IMDG

UN Number UN1950 UN PROPER SHIPPING NAME AEROSOLS

Transport Hazard Class(es) 2.1
Subsidiary class(es) Marine Pollutant No
Labels Required 2.1

Special Precautions Read safety instructions, SDS and emergency procedures before handling

Transport in bulk Not applicable

Annex II of MARPOL 73/78

and the IBC Code

## **SECTION 15 - REGULATORY INFORMATION**

# SAFETY, HEALTH AND ENVIRONMENTAL REGULATIONS/LEGISLATION SPECIFIC FOR THE SUBSTANCE OR MIXTURE

#### **EU REGULATIONS**

Regulation (EC) No. 2037/2000 on substance that deplete the ozone layer, Annex I

Regulation (EC) No. 2037/2000 on substance that deplete the ozone layer, Annex II Not listed

Regulation (EC) No. 850/2004 on persistent organic pollutants, Annex I Not listed

Regulation (EC) No. 689/2008 concerning the export and import of dangerous chemicals, Annex I, Part 1 Not listed

Regulation (EC) No. 689/2008 concerning the export and import of dangerous chemicals, Annex 1, Part 2 Not listed

Regulation (EC) No. 689/2008 concerning the export and import of dangerous chemicals, Annex I, Part 3 Not listed

SAFETY DATA SHEET

MATERIAL NAME: HYLOMAR M AEROSOL 710XX362

EMERGENCY TELEPHONE NO.: CALL INFOTRAC AT 1-800-535-5053

**PRODUCT INFORMATION NO.:** (513) 874-6550

**DATE ISSUED: FEBRUARY 1, 2018** 

#### **SECTION 15 - REGULATORY INFORMATION (CONT)**

Regulation (EC) No. 689/2008 concerning the export and import of dangerous chemicals, Annex V Not listed

Directive 96/61/EC concerning integrated pollution prevention and control (IPPC): Article 15, European Pollution Emission Registery (EPER)

Not listed

Regulation (EC) No. 1907/2006, REACH Article 59(1). Candidate List Not listed

OTHER REGULATIONS This product is classified and labeled in accordance with EC directives or

respective national laws. This Safety Data Sheet complies with the requirements

of Regulation (EC) No 1907/2006

NATIONAL REGULATIONS Not available

CHEMICAL SAFETY ASSESSMENT

No Chemical Safety Assessment has been carried out.

# **SECTION 16 – OTHER INFORMATION**

#### LIST OF ABBREVIATIONS

CLP: Regulation No. 1272/2008 DNEL: Derived No-Effect Level

PNEC: Predicted No-Effect Concentration

REFERENCES Not available

## INFORMATION ON EVALUATION METHOD LEADING TO THE CLASSIFICATION OF MIXTURE

The mixture is classified based on test data for physical hazards. The classification for health and environmental hazards is derived by a combination of calculation methods and test data, if available. For details see Sections 9, 11 and 12

#### FULL TEXT OF ANY STATEMENTS OR R-PHRASES AND H-PHRASES UNDER SECTIONS 2 TO 15

R11 Highly flammable
R12 Extremely flammable
R36 Irritating to eyes

R66 Repeated exposure may cause skin dryness or cracking

R67 Vapors may cause drowsiness and dizziness

H220 Extremely flammable gas
H225 Highly flammable liquid and vapor
H319 Causes serious eye irritation
H336 May cause drowsiness or dizziness
H371 May cause damage to organs

#### TRAINING INFORMATION

Follow training instructions when handling this material

TO THE BEST OF OUR KNOWLEDGE, THE INFORMATION CONTAINED HEREIN IS ACCURATE; OBTAINED FROM SOURCES BELIEVED BY VALCO CINCINNATI, INC. TO BE ACCURATE. SINCE THE CONDITIONS AND METHODS OF USE OF OUR PRODUCT ARE BEYOND OUR CONTROL, WE DISCLAIM ANY AND ALL LIABILITY ARISING OUT OF THE IMPROPER USE OF THIS PRODUCT OR THE INFORMATION PROVIDED HEREWITH.